



Specifications:

Model	Diamond 10	Diamond 11	Diamond 12	Diamond 13
General description	2-way bookshelf speaker	2-way bookshelf speaker	2-way bookshelf speaker	2.5-way floorstanding speaker
Base driver	4" (103mm) Woven Kevlar Cone	5 1/8" (139mm) Woven Kevlar Cone	6.5" (165mm) Woven Kevlar Cone	5 1/8" (139mm) Woven Kevlar Cone
Midrange driver	1 1/2" (38mm) Soft Dome	1 1/2" (38mm) Soft Dome	1 1/2" (38mm) Soft Dome	1 1/2" (38mm) Soft Dome
Speaker enclosure	87dB	87dB	88dB	90dB
Sensitivity (CBY 2m)	40 (Compatible 80)	40 (Compatible 80)	40 (Compatible 80)	40 (Compatible 80)
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
Frequency Response (V-3dB)	75Hz - 20kHz	55Hz - 20kHz	48Hz - 20kHz	44Hz - 20kHz
Dimensions (mm)				
Height (optional)	360mm	360mm	360mm	615-550mm
Width	150mm	150mm	220mm	190mm
Depth (with terminal)	440-100mm	440-100mm	420-90mm	440-90mm



Model	Diamond 14	Diamond 15	Diamond 11CS	Diamond 11SR
General description	3-way floorstanding speaker	3-way floorstanding speaker	2-way center speaker	2-way surround speaker
Base driver	6.5" (165mm) Woven Kevlar Cone	8" (203mm) Woven Kevlar Cone	4" (103mm) Woven Kevlar Cone	5 1/8" (139mm) Woven Kevlar Cone
Midrange driver	1 1/2" (38mm) Soft Dome	1 1/2" (38mm) Soft Dome	1 1/2" (38mm) Soft Dome	1 1/2" (38mm) Soft Dome
Speaker enclosure	90dB	90dB	87dB	89dB
Sensitivity (CBY 2m)	40	40	40 (Compatible 80)	40 (Compatible 80)
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
Frequency Response (V-3dB)	48Hz - 20kHz	39Hz - 20kHz	89Hz - 20kHz	69Hz - 20kHz
Dimensions (mm)				
Height (optional)	615-550mm	1125-950mm	145-100mm	170-100mm
Width	220mm	220mm	40mm	40mm
Depth (with terminal)	420-90mm	430-90mm	130-90mm	120-90mm