



Listening is believing

An addition to our top-of-the-range Custom Theatre 800 Series, which brings the same legendary technology used in B&W's 800 Series of stand-alone speakers to your home theatre set-up. The CT8.4 LCRS is designed as an alternative to the CT8 DS side/rear channel speaker when space is at a premium:

it's a smaller, more compact vertical surround sound speaker that generates exactly the same authentically three-dimensional listening experience. The CT8.4 LCRS also packs enough power to act as a stand-alone loudspeaker positioned front, side and rear within a complete custom theatre system.

Technical Specifications

Technical features

Nautilus™ tube-loaded tweeter
Aramid Fibre FST midrange cone
Carbon fibre/Rohacell® bass unit cone
Speakon® and binding post connectors

Description	3-way closed-box system
Drive units	1x ø32mm (1.2 in) tube loaded aluminium dome high-frequency 1 x ø150mm (6 in) woven Aramid Fibre FST™ mid-range 1 x 200mm (8 in) carbon fibre/Rohacell® sandwich cone bass
Frequency range	-6dB at 39Hz and 40kHz
Frequency response	49Hz – 24kHz ±3dB on reference axis
Dispersion	Within 2dB of reference response Horizontal: over 60° arc Vertical: over 10° arc
Sensitivity	88dB spl (2.83V, 1m)
Harmonic distortion	2nd and 3rd harmonics (90dB, 1m) <1% 80Hz – 20kHz <0.5% 200Hz – 20kHz
Nominal impedance	8Ω (minimum 3.0Ω)
Crossover frequency	380Hz, 4kHz
Recommended amplifier power	50W – 200W into 8Ω on unclipped programme
Max. recommended cable impedance	0.1Ω
Dimensions	Height: 630mm (24.8 in) Width: 325mm (12.8 in) Depth: 185mm (7.3 in) Depth with grille: 227mm (9 in)
Net Weight	21.0kg (46.3 lb)
Finishes	Cabinet Black painted

